

# NOBUS



## HIGH WALL MOUNTED TYPE FAN COIL UNIT

- 1: Digital display panel
- 2: Remote controller
- 3: Stainless steel hose, let the water connection easily (optional)
- 4: Power down memory function



▶ Performance

### High wall mounted FCU standard type

Model ( 2 – tube system)			FC-02WM	FC-03WM	FC-04WM	FC-05WM	FC-06WM	FC-08WM	
Power supply			220V,50Hz, 1Ph						
Air volume	H	m <sup>3</sup> /h	340	510	680	850	1020	1360	
	M		260	380	515	650	765	1010	
	L		180	260	340	43	520	700	
Static pressure		Pa	0	0	0	0	0	0	
Cooling capacity	TH	H	W	1800	2700	3600	4500	5400	7200
			BTU/h	6142	9212	12283	15354	18425	24566
			W	1350	2025	2700	3375	4050	5400
			BTU/h	4606	6909	9212	11516	13819	18424
	SH	M	W	1476	2214	2952	3690	4428	5904
			W	978	1399	1963	2409	3044	3926
	TH	L	W	1098	1647	2196	2745	3294	4392
			W	649	960	1355	1715	2060	2710
Heating capacity	H		W	2700	4050	5400	6750	8100	10800
	M		W	2146	3219	4293	5366	6439	8586
	L		W	1512	2268	3024	3780	4536	6048
Noise	High speed		dB(A)	0.31	0.46	0.62	0.77	0.93	1.24
Powerinput	High speed		W	12	14	17	18	22.5	23.5
Waterflow volume	High speed		m <sup>3</sup> /h	57	67	74	82	55	65
Pressure dropping			kPa	86	100	110	122	83	97
Water tube connection(inlet)			ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	
Water tube connection(outlet)			ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	
Coil		Type	Hydrophilic aluminum fin to wear copper tube						
Maximum working pressure			MPa	1.6	1.6	1.6	1.6	1.6	1.6
Condensing water pipe			mm	φ 16	φ 16	φ 16	φ 16	φ 16	φ 16
Net dimension	L × W × H		mm	850X300X198	850X300X198	970X315X235	970X315X235	1100X330X235	1100X330X235
Net weight			kg	11	11	15	15	20	20